



Liberty Suppressors, LLC  
113 Gunsmoke Trail  
Trenton, GA 30752-5156  
Phone: 706-661-6911  
FAX: 706-229-6400  
[info@libertycans.net](mailto:info@libertycans.net)  
[www.Libertycans.net](http://www.Libertycans.net)

Hello to the newest owner of a Liberty Regulator Silencer!!!

We are immensely happy that you chose our suppressor for your 22LR applications. We are sure you will enjoy it as much as we do.

As a note to help with disassembly in the future, we wanted to take a moment to give you a little tip to keep frustration to a minimum.

The rear over-cap of the regulator is LEFT HAND THREADS. PLEASE REMEMBER THIS DURING DISASSEMBLY. Also, you will notice that under the over cap is a hex protrusion just begging for a 5/8" wrench. Please refrain from putting said wrench on this hex, as it isn't needed to remove the cap except to maintain the unit here at Liberty should there be a problem. This insert is retained with Loctite and will be difficult to remove. If it is removed from the core, special care should be taken to insure there is no materials or foreign substances between the mating surfaces of the two parts and that the parts are not over tightened and a small amount of blue Loctite is placed on the threads when reassembled.

Other than that, this unit is pretty straightforward for maintenance and use, enjoy!

The Liberty Team

**WARNING: READ THIS  
BEFORE ATTEMPTING  
TO DISMANTLE YOUR  
SUPPRESSOR!!!**